

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-142199

(43)Date of publication of application : 25.05.2001

(51)Int.Cl.

G03F 7/004

G03F 7/039

G03F 7/40

H01L 21/027

(21)Application number : 11-323332

(71)Applicant : SHIN ETSU CHEM CO LTD

(22)Date of filing : 12.11.1999

(72)Inventor : TAKEMURA KATSUYA

KOIZUMI KENJI

KANEKO TATSUSHI


SAKURADA TOYOHISA

## (54) CHEMICALLY SENSITIZED POSITIVE RESIST MATERIAL AND PATTERN FORMING METHOD


### (57)Abstract:

PROBLEM TO BE SOLVED: To form a minute contact hole pattern for the production of a very large scale integrated circuit as well as to provide a highly adaptable process in which the reduction of contact hole size by heating is easily controlled by adding a compound having, in one molecule, two or more functional groups which can crosslink with a polymer compound used in a chemically sensitized positive resist material in a step for reducing contact hole size by heating a contact hole pattern when the contact hole pattern is formed using the resist material.


SOLUTION: The objective chemically sensitized positive resist material for forming a contact hole pattern by a thermal flow process contains a compound containing two or more functional groups of formulae (1)-a, (1)-b and (1)-c in one molecule. In the formulae, R1-R4 are each H or linear, branched or cyclic alkyl; R5-R9 are each linear, branched or cyclic alkyl; and adjacent symbols Rn may combine to each other to form a ring.



(1)-a



(1)-b



(1)-c